

ACTWELL

LIGHTING



TECHNICAL INFORMATION

AW51-1RD ECOFIRE 15 IP65

APPLICATION AREA



Aged Care



Child Care



Commercial



Educational Facilities



Hospitality



Hospital and Medical



Hotels



Infrastructure



Retail



Shopping Centers



Residential



Sports Centers



Actwell Trading reserves the right to make revisions and updates.
If you have any enquiries please consult an Actwell Lighting Representative



34 Mary Parade
Rydalmere NSW 2116 Australia



+61 2 9638 3333



enquiries@actwelllighting.com.au

PRODUCT NAME	
ECOFIRE 15 IP65	
Description	Cyanosis Approved Option, Patented Heat Sink for Rapid Heat Dissipation, Fixed, Anti-Glare, High CRI, Low Profile, IP65 Rated Water & Dust Protection, Recessed LED Downlight
Materials	Aluminium Powder Coated Trim and Body, Two Step Parabolic Reflector, Clear Glass Diffuser, Custom Engineered Heat Sink, Aluminium Recessing Side Blades
Dimensions	Diameter: 87mm; Height: 65mm; Cut Out: 80mm
Driver	350mA Remote LED Driver
Luminaire Details	15W, 2700K/3000K/4000K Available, CRI> 90/94, COI: 0.48, Beam Angle: 24°/36°/60°, SDCM<3, UGR<16, 1575 Lumens, 1100 Luminaire Luminous Flux at 3000K. Lumen Efficacy: 105Lm/W.
Ratings	IP65 IC-4 IK05
Rated Life	5yr Warranty LM80 B10: 65,000 hrs <i>Environmental Impact: Luminaire > 95% Recyclable, Fitting Under Actwell Revitalisation Program to Refit Parts to End Waste</i>
Installation	Recessed

Actwell Trading reserves the right to make revisions and updates.
If you have any enquiries please consult an Actwell Lighting Representative



34 Mary Parade
Rydalmere NSW 2116 Australia



+61 2 9638 3333



enquiries@actwelllighting.com.au

ORDER CODE


AW51-1RD- (Colour Finish)-(Temperature)-(Beam Angle)-(Dimming)

Example: AW51-1CYN-WH-3K-60°-ND

OPTIONS

Cyanosis Option	Colour Finish	Temperature	Beam Angle	Dimming
Replace 'RD' with 'CYN'	WH (White)	2.7K (2700K)	24°	ND (Non-Dim)
	BK (Black)	3K (3000K)	36°	PH (Phase-Dim)
		4K (4000K)	60°	11 (1-10V Dim)
				DD (DALI-Dim)

DIMENSION LINE DIAGRAM



Actwell Trading reserves the right to make revisions and updates.
If you have any enquiries please consult an Actwell Lighting Representative



34 Mary Parade
Rydalmere NSW 2116 Australia




+61 2 9638 3333




enquiries@actwelllighting.com.au


PHOTOMETRICS



h(m)	D(m)	Em(lx)	Emax(lx)
			24°
1	0.4	2812	4633
2	0.8	703	1158
3	1.2	313	515
4	1.6	176	290



h(m)	D(m)	Em(lx)	Emax(lx)
			36°
1	0.6	1524	2409
2	1.3	381	602
3	1.9	169	268
4	2.6	95	151



h(m)	D(m)	Em(lx)	Emax(lx)
			60°
1	1.0	835	1421
2	2.1	209	355
3	3.1	93	158
4	4.2	52	89

Actwell Trading reserves the right to make revisions and updates.
If you have any enquiries please consult an Actwell Lighting Representative



34 Mary Parade
Rydalmere NSW 2116 Australia




+61 2 9638 3333



enquiries@actwelllighting.com.au

PRODUCT APPLICATION PHOTOS



V1

Actwell Trading reserves the right to make revisions and updates.
If you have any enquiries please consult an Actwell Lighting Representative



34 Mary Parade
Rydalmere NSW 2116 Australia



+61 2 9638 3333



enquiries@actwelllighting.com.au