



# TECHNICAL INFORMATION AW11-3RD FLUTE



#### **APPLICATION AREA**



**Aged Care** 



Child Care



Hospitality



Hospital and Medical



**#** 

Retail



**Shopping Centers** 



Residential



Commercial



Theatre



Cabinetry



Sports Centers



Hotels





PRODUCT NAME				
FLUTE				
Description	Miniature, Slender, Deep Baffle, Fixed, Recessed LED  Downlight			
Material	Pure Aluminium Housing and Trim, Polycarbonate Diffuser			
Dimension	Diameter: 60mm; Height: 83mm; Cut Out: 55mm			
Driver	Remote LED Driver			
Luminaire Details	6.5W, 2700K/3000K/4000K Available, CRI>90,  Beam Angle: 15°/24°/36°/50°, SDCM<3, UGR<17,  940 Lumens, 820 Luminaire Luminous Flux at 3000K 36°.  Lumen Efficacy: 145Lm/W			
Ratings	IP44   IC-4   IK07			
Rated Life	5yr Warranty   L80 B10: 67,000hrs  Environmental Impact: Luminaire > 95% Recyclable, Fitting Under Actwell Revitalisation Program to Refit Parts to End Waste			
Installation	Recessed			









#### **ORDER CODE**


AW11-3RD-(Colour Finish)-(Temperature)- (Beam Angle)- (Dimming)

Example: AW11-3RD-WH-3K-50°-ND

#### **OPTIONS**

Colour Finish	Temperature	Beam Angle	Dimming
WH (White)	2.7K (2700K)	15°	ND (Non-Dim)
BK (Black)	3K (3000K)	24°	PH (Phase-Dim)
	4K (4000K)	36°	DD (DALI-Dim)
		50°	

#### **DIMENSION LINE DIAGRAM**










#### **PHOTOMETRICS**



### **PRODUCT APPLICATION PHOTOS**

